

31 Jul 2026

TECHNICAL SPECIFICATION SHEET

HYDROGENATED CASTOR OIL FLAKES	
CHARACTERISTICS	SPECIFICATION
△ MELTING POINT (DROP POINT)	85 – 88°C
△ ACID VALUE	2.0 MG KOH/G MAX
△ SAPONIFICATION VALUE	176 – 182 MG KOH/G
△ IODINE VALUE	1.0 MAX
◇ MOISTURE	0.5% MAX

(This report is computer generated and therefore does not require any signature.)

(For industrial use only. Not for fertilizer/oral/food or medical use)
(Marketed by Suraj Chemicals, manufactured by independent or contracted third-party facilities)

"ACIDS, SOLVENTS, MINERALS, BASES AND SPECIALISED CHEMICAL COMPOUNDS"

+91 - 7092722822, +91 - 9840284032
+91 - 44 - 25393652, 42130281
sales@surajchemicals.com
surajchemicals@yahoo.com

No 92, Govindappa Naicken Street
Shiva Complex, Chennai - 600001
www.surajchemicals.com
GST NO : 33ACEPV8190L1ZZ

EXCLUSIVE FOR GRASIM INDUSTRIES (ADITYA BIRLA), BASF (GERMANY), GODREJ INDUSTRIES, SNF (FRANCE)