

06 Aug 2026

TECHNICAL SPECIFICATION SHEET

PRECIPITATED SILICA	
CHARACTERISTICS	SPECIFICATION
△ SIO ₂ CONTENT	98% MIN
△ SPECIFIC SURFACE AREA (BET)	100 – 200 M ² /G, TYPICAL
○ MOISTURE	6% MAX
△ PH (5% AQUEOUS SUSPENSION)	6.5 – 7.5
△ OIL ABSORPTION	150 – 300 G/100G

(This report is computer generated and therefore does not require any signature.)

(For industrial use only. Not for fertilizer/oral/food or medical use)
(Marketed by Suraj Chemicals, manufactured by independent or contracted third-party facilities)

"ACIDS, SOLVENTS, MINERALS, BASES AND SPECIALISED CHEMICAL COMPOUNDS"

+91 - 7092722822, +91 - 9840284032
+91 - 44 - 25393652, 42130281
sales@surajchemicals.com
surajchemicals@yahoo.com

No 92, Govindappa Naicken Street
Shiva Complex, Chennai - 600001
www.surajchemicals.com
GST NO : 33ACEPV8190L1ZZ

EXCLUSIVE FOR GRASIM INDUSTRIES (ADITYA BIRLA), BASF (GERMANY), GODREJ INDUSTRIES, SNF (FRANCE)