

02 Aug 2026

TECHNICAL SPECIFICATION SHEET

VYTAL 3310 — LIQUID COAGULANT FOR RESIN/EPOXY EFFLUENT

CHARACTERISTICS	SPECIFICATION
⊙ PHYSICAL FORM	PALE YELLOW TO COLOURLESS LIQUID
△ AL ₂ O ₃ CONTENT	TYPICAL VALUE — REFER TO CURRENT SPECIFICATION SHEET
△ PH (5% SOLUTION)	TYPICAL VALUE — REFER TO CURRENT SPECIFICATION SHEET
△ NSF/ANSI/CAN 60 CERTIFICATION	CERTIFIED BY GRASIM INDUSTRIES LTD. — MAX DOSAGE 200 MG/L

(This report is computer generated and therefore does not require any signature.)

*(For industrial use only. Not for fertilizer/oral/food or medical use)
(Marketed by Suraj Chemicals, manufactured by independent or contracted third-party facilities)*

"ACIDS, SOLVENTS, MINERALS, BASES AND SPECIALISED CHEMICAL COMPOUNDS"

+91 - 7092722822, +91 - 9840284032
+91 - 44 - 25393652, 42130281
sales@surajchemicals.com
surajchemicals@yahoo.com

No 92, Govindappa Naicken Street
Shiva Complex, Chennai - 600001
www.surajchemicals.com
GST NO : 33ACEPV8190L1ZZ

EXCLUSIVE FOR GRASIM INDUSTRIES (ADITYA BIRLA), BASF (GERMANY), GODREJ INDUSTRIES, SNF (FRANCE)